

# MarkTag Classic

DATASHEET

The MarkTag Classic is the high-end choice for long-range in parking and access control



## KEY FEATURES

- ▶ Highly reliable long-range tag
- ▶ Can be read in any orientation
- ▶ Licence-free worldwide

The MarkTag Classic is a long-time proven high-end choice for vehicle identification within parking and access control. Easy to use, highly reliable, can be read from both sides, and is licence-free worldwide as it is using the 2.45GHz frequency band. The tag is placed behind the windshield using an easily installed WinFix.

The tag has a pre-programmed 8-digit unique identity code. A 32-bit checksum ensures a correct reading.

The tag emits no radio signals, it only reflects a modulated response to a reader request. As the tag electronics are always powered up and the power consumption is constant, the tag lifetime is fully predictable +6 years independently of the number of reads. As battery levels are getting low, the tag generates a battery low alarm to the reader, which can then inform the host systems.

PART NO.	INFORMATION	DESCRIPTION
125500,	MarkTag Classic	Tag for use with LR-6
195100,	Winfix	Holder for MarkTag Classic

[www.tagitalia.com](http://www.tagitalia.com)   [info@tagitalia.com](mailto:info@tagitalia.com)

**GENERALE**  
SISTEMI

**TAGITALIA**  
RFID System & Technologies

**TagMaster**  
LEARN FROM REALITY

## TECHNICAL INFORMATION

<b>Operating frequencies</b>	2.435 GHz to 2.465 GHz
<b>Read range</b>	Up to 6 metres (20 ft) *
<b>Read mode</b>	Random
<b>Dimensions</b>	86 x 54 x 4 mm (3.39 x 2.13 x 0.16 inch)
<b>Weight</b>	18g (0.04 lbs)
<b>Material</b>	Polymer
<b>Battery lifetime</b>	Typically +6 years. Lifetime is dependent on temperature.
<b>Operating temperature</b>	-20°C (-4°F) to +85°C (+185°F)
<b>Protection</b>	IP54
<b>Colour</b>	Light grey with white back
<b>Certifications</b>	Electrical Safety EN 62368-1 Health 1999/519/EC Radio RED 2014/53/EC, EN 300 440 v2.1.1 EMC EN 301489-3 RoHS, WEEE

\* Read range depends on reader settings.

Due to TagMaster's continuous effort to develop the products in response to customer needs, the above specifications are subject to change.